

REVISIONS
REV
DESCRIPTION
DRFTG
APP BY
DATE
CANNON 2DE19S
UP TO SPEED
FEED HOLE
PUN START
PUN BUSY (0)
PUN COMPLETE
PUNCH FEED
COMMON SELECT
PUN SELECT
DATA OUT A
PUN 0
PUN 1
PUN 2
PUN 3
PUN 4
PUN 5
PUN 6
PUN 7
DATA 8
DATA 9
DATA 10
DATA 11
DATA 12
DATA 13
DATA 14
DATA 15
USED WITH OPTION NO. 4013
PUN INT DISABLE (0)
PUN DONE (1)
RQENB
INTR
MSKO
DATA 13
PWR ON
IO RESET
START
CLEAR
PUN BUSY (1)
SELD
SELB
INT ACK
PUN INT REQ (1)
PUN ACK
DATA IN A
OUT OF TAPE
NOTE: CAPACITORS C37, C48, C49, C61, C62, C71, C75, & C76 ARE .06 MFD FILTERS, AND AS SUCH ARE NOT SHOWN ON THIS DRAWING.
UNLESS OTHERWISE SPECIFIED— DIMENSIONS ARE IN INCHES TOLERANCES ON FRACTIONS DECIMALS ANGLES ± .XX ± .XXX ± ± PARTS TO BE FREE FROM BURRS BREAK ALL EDGES .010
UNLESS OTHERWISE SPECIFIED - ALL MACH. SURFACES
MATERIAL
FINISH
QTY.
DESCRIPTION
PART NO.
DRAWN
CHECKED
ENGINEER
APPROVED
FIRST USED ON
SHEET 1 OF 1
DATA GENERAL CORPORATION
TITLE
PAPER TAPE PUNCH CONTROL 4012
SIZE D
CODE 001
DRAWING NUMBER 000073
REV 02