

SECTION B: VERIFIED TAPE DRIVES

Legend: SS = Start/Stop, S = Streamer, SS/S = Start/Stop & Streamer

Drive Model	800 bpl (NRZI)			1600 bpl (PE)			6250 bpl (GCR)		
	type	ips	KB/sec	type	ips	KB/sec	type	ips	KB/sec
Cipher F880				S	100	160			
CDC 92185-01				S	75	120	S	75	469
Fujitsu 2442*				S	100	160	S	100	625
Fujitsu 2444*				S	75	120	S	75	469
Fujitsu 2436				SS/S	200	320	SS/S	200	1250
Kennedy 9400	SS	75	60	SS	75	120	SS	45	281
Kennedy 9600	S	100	80	S	100	160			
Kennedy 9610	SS	50	40	SS	100	160	SS	100	625
STC 2921				SS	50	80	SS	50	312
STC 2922				SS/S	100	160	SS/S	100	625
Telex 9251	SS	50	40	SS	50	80	SS	50	312

Megatape MT500: streams at 180 ips (10,666 bpl), resulting in 250 KB/sec.

Megatape MT750: streams at 180 ips (16,000 bpl), resulting in 250 KB/sec.

*The optional CACHE buffer has not yet been tested in Zetaco labs.

SECTION C: If you know of devices, other than those listed in Section B, that are running with BMX-2, please write or telex our Customer Support Group with the information so they can be added to this section.